



FTTX / Broadband Installation Fiber & RJ45 /
Comprehensive Testing Tool OPM / RJ45 Sequence
RJ 45 Tracker / LED light



FEATURES

- ※ Wavelength Memory Function
- ※ RJ45 Sequence
- ※ RJ45 Tracker
- ※ Support user calibration
- ※ Supporting SC /FC / ST Interface
- ※ VF 2mW – Aprox 2-3 Km
- ※ Automatic Shutdown
- ※ Supporting Simultaneous Linear (mW) and Non-Linear (dBm) display.

MORE INFO



RJ 45 Port with Mini USB



Power Meter SC/ FC / ST
with VFL Port



Smart RJ45 Sequence &
Tacker

SPECIFICATIONS

Wavelength	800-1700nm	800-1700nm
Connector	Replaceable FC/SC/ST	
Type of Connector	InGaAs	InGaAs
Measurement range	-70 ~ +6 (dBm)	-50~ +26(dBm)
Uncertainty	±5%	
Wavelength (nm)	850, 980, 1300, 1310, 1490, 1550, 1625, 1650	
Display resolution	Linear display: 0.1% logarithmic display: 0.01dBm	
650nm (Optional)	1mW/1-mW/20mW/30mW/50mW	
Operating Temperature	-10~+60 °C	
Storage Temperature	-30~+70 °C	
Automatic Shutdown	10 Min	
Working Hours	AA Batteries - Continuously OPM ≥ 72 h	
	AA Batteries - Continuously use VFL ≥ 10Min	
	Li battery is 700mAh Li battery - (Only in FG-PM 600L)	
	Continuously use VFL ≥ 10Min	
Instrument Dimension	112 x 66 x 30 mm	
Power Supply	Two Segment AA Batteries	
	USB Charging Cable (Only in FG-PM 600L)	
Net Weight	140g/150g	

PACKAGE

